

spc-75-30

Assembly instructions

This VESA adapter is compatible with all monitors that have the VESA standard 75x75 mm.

△ WARNING

To minimize the risk of injury, it is important to read all instructions carefully before installation. We accept no liability for personal or material damage caused by improper use of this product.

Also, be sure to pay attention to the technical specifications of the product.

- 1. Read all instructions thoroughly.
- **2.** A faulty installation can lead to damage or serious injury. Ensure that the product and the monitor are securely mounted before use.
- **3.** Make sure that the mount to which the product is attached can easily support the total weight of the monitor, computer, and adapter.



Technical Specifications

Maximum monitor weight: 7 kg / 15.4 lbs
 VESA standard compatibility: 75x75 mm

• Material: plastic

• Pivot angle: compatible (90°)

Maximum operating temperature: 35°C / 95°F
 Maximum ambient temperature: 35°C / 95°F

△ WARNING

Exceeding the maximum load capacity, operating temperature or ambient temperature can lead to serious injury or damage.

Important Safeguards



Please read this manual carefully and keep it for future reference. If you pass the product on to third parties, this manual should always be included. Ignoring these instructions may result in injuries or damage to people and products, for which we cannot accept any liability.

IMPORTANT - KEEP FOR FUTURE REFERENCE.

- The use of this product should always be in accordance with the specified safety instructions.
- Do not install your VESA adapter in combination with the monitor in places where people are located below.
- Do not exceed the maximum weight of the compatible monitor models, as this may result in serious injuries or property damage.
- Pay attention to the maximum ambient temperature of 35°C when using the product.
- Do not mount the VESA adapter near a heat source or in direct sunlight, as this may cause the adapter to overheat.
- Check if your mounting point (e.g., monitor arm) can support the weight of the monitor with the VESA adapter.
- The product is designed exclusively for mounting with a hole pattern of 75x75 / 100x100mm / 200x200mm.
- After installing the VESA adapter, the position of the monitor must be readjusted to ensure proper ergonomics.

△ WARNING

Ensure that the device is turned off and disconnected from the power supply before installation to avoid possible injuries or damage.

1. Before First Use

Check the product carefully for possible transport damage and for the absence of accessories, such as screws, which should be included in the scope of delivery.

A CAUTION

Make sure that packaging materials and small screws and parts contained therein are inaccessible to children to minimize the risk of choking and other risks.

2. Maintenance and Cleaning

2.1 Maintenance

- It is recommended to check every three months that all screws are still tight. Also, regularly check the condition of all components of the product.
- Store the product in a cool and safe place, ideally at a maximum storage temperature of 40°C. For additional safety, keep the product away from children and preferably in its original packaging.
- Avoid any vibrations and shocks so as not to affect the life and functionality of the product.

2.2 Cleaning

- No corrosive or hot cleaning agents should be used to clean the product. Likewise, wire brushes, metal or other sharp materials are unsuitable for cleaning and should not be used.
- For gentle and effective cleaning, the use of a soft, damp cloth is recommended.

3. Waste Disposal

For the disposal of this product we recommend to contact the responsible local authorities or disposal services. They can provide you with detailed information on available disposal options and recycling centers in your area.

4. Manufacturer Information

3idee S.à r.l. 19 Rue de Bitbourg L-1273 Luxembourg Luxembourg

mail: info@3idee.eu

5. Help and Feedback

If you need help with your article, we are here for you. We also appreciate any feedback.

https://help.3idee.eu/en/contact

Scope of Delivery Accessories



4x M4x40 screw with cross slot (**SP13**)

4x M4x45 screw with cross slot (**SP31**)

▲ NOTE: Please check before assembly that all accessory parts are complete. If anything is missing, please contact our customer service immediately via email or phone. We are happy to assist you.

Horizontal / Vertical Alignment

Not all VESA adapters and monitors are suitable for vertical alignment. (upright)

This is due to the geometry of the adapter / monitor, which in some cases cannot be achieved in any other way.

We would like to point out that this information should not be disregarded under any circumstances, as the adapter will very quickly reach its durability limit if it is not mounted as specified.

We always try to develop monitors for vertical (upright) mounting.

The standard orientation of a monitor is horizontal.

Horizontal Mounting: YES



Vertical Mounting: YES



General Dimensions

VESA hole size: 75mm x 75mm


VESA hole ø: 4.7mm


Inner Dimension a: 55mm x 55mm

Outer Dimension a: 67.4mm

Height: 30mm

Outer dimensions: 85mm x 85mm





Assembly Instruction

Step 1

Attach the spacer as shown between your monitor and your monitor arm / VESA mount. (Figure 1)

Use the screws from (SP31).

▲ **NOTE:** If the instructions provided in this step are not suitable for your device, please follow the mounting guidelines of your monitor arm or swivel arm manufacturer to attach the monitor to the wall or swivel arm.




Figure 1